

221 Series

The Way to Connect!



WAGO 221

COMPACT Splicing Connectors for All Conductor Types



221-413, 4 mm² variant

- Continuous operating temperature: max. 105 °C
- Surrounding air temperature: max. 85 °C (T85)











Carrier				
	Description	Item No.	Pack. Unit	
·	Strain relief plate, mounts on 221-500 and 221-510	222-505	50	
	Mounting carrier, orange, for 2-, 3- and 5-wire connectors, 4 mm ² variant	221-500	50	
	Mounting carrier, orange, for 2-, 3- and 5-wire connectors, 6 mm ² variant	221-510	50	
	Angled DIN-rail adapter, for horizontal 221-500 mounting on DIN-35 rail	222-510	50	
The state of the s	Mounting carrier, blue, for 2-, 3- and 5-wire connectors, 4 mm² variant	221-500/ 000-0006	50	
	Mounting carrier, blue, for 2-, 3- and 5-wire connectors, 6 mm² variant	221-510/ 000-006	50	
THE PARTY OF THE P	Mounting carrier, gray-yel- low, for 2-, 3- and 5-wire connectors, 4 mm² variant	221-500/ 000-053	50	
	Mounting carrier, gray-yel- low, for 2-, 3- and 5-wire connectors, 6 mm² variant	221-510/ 000-053	50	

4 mm² Variant				
0.14 4 mm ² 0.2 4 mm ² (24 12 AWG)		450 V / 4 kV / 32 A	2	
	Description		Item No.	Pack. Unit
	2-wire conne	ectors	221-412	100
	3-wire conne	ectors	221-413	50
	5-wire conne	ectors	221-415	25

6 mm² Variant				
0.5 6 mm ² (20 10 AWG)		450 V / 4 kV / 41 A	2	
	Description		Item No.	Pack. Unit
	2-wire conne	ectors	221-612	50
	3-wire conne	ectors	221-613	30
	5-wire connectors		221-615	15
O				
Carrier				
	Description		Item No.	Pack. Unit

Carrier			
	Description	Item No.	Pack. Unit
	Mounting carrier, for 2-wire connectors, screw mounting	221-502	50
	Mounting carrier, for 3-wire connectors, screw mounting	221-503	50
	Mounting carrier, for 5-wire connectors, screw mounting	221-505	50



Two test slots



Industry's widest range of conductor sizes

 Combine any type and size of conductors



Transparent housing

Clearly identify if the conductor has been stripped and inserted properly

info@wago.com - www.wago.com/221